



B Drive Anchor

- Used for attaching cable straps, cable clamps, ground blocks, etc. to concrete, block, brick, and stone.
- Comprised of a Zamac shell (Type 3) or a stamped steel shell (Type 1) and a flat head nail.
- Manufactured from AISI 1008 Steel.
- Zinc plated to meet ASTM Specification B633, Class SC4, Type 1.
- Type 3 B Drive Anchors (Hammer Drive Anchors) are offered in $\frac{3}{16}$ " and $\frac{1}{4}$ " diameters only.
- Type 1 B Drive Anchors are offered in $\frac{5}{16}$ ", $\frac{3}{8}$ ", and $\frac{1}{2}$ ".
- Not recommended for overhead applications.
- Manufactured in the United States.

| PART NUMBER | SIZE | HOLE SIZE | BELL NUMBER | STD PKG |
|-------------|-------------------------------------|------------------|-------------|---------|
| 316 | $\frac{3}{16}$ " x $\frac{7}{8}$ " | $\frac{3}{16}$ " | 400002796 | 8 |
| 92 | $\frac{3}{16}$ " x $\frac{7}{8}$ " | $\frac{3}{16}$ " | | 100 |
| 655 | $\frac{3}{16}$ " x $1\frac{1}{4}$ " | $\frac{3}{16}$ " | 400002804 | 8 |
| 317 | $\frac{1}{4}$ " x 1" | $\frac{1}{4}$ " | 400002812 | 8 |
| 93 | $\frac{1}{4}$ " x 1" | $\frac{1}{4}$ " | | 100 |
| 318 | $\frac{1}{4}$ " x $1\frac{1}{4}$ " | $\frac{1}{4}$ " | 400002820 | 8 |
| 94 | $\frac{1}{4}$ " x $1\frac{1}{4}$ " | $\frac{1}{4}$ " | | 100 |
| 380 | $\frac{1}{4}$ " x $1\frac{1}{2}$ " | $\frac{1}{4}$ " | 400002853 | 8 |
| 412 | $\frac{1}{4}$ " x 2" | $\frac{1}{4}$ " | | 8 |
| 319 | $\frac{5}{16}$ " x $1\frac{1}{4}$ " | $\frac{5}{16}$ " | 400002846 | 8 |
| 320 | $\frac{5}{16}$ " x $1\frac{3}{4}$ " | $\frac{5}{16}$ " | 400002853 | 8 |
| 321 | $\frac{5}{16}$ " x $2\frac{1}{4}$ " | $\frac{5}{16}$ " | 400002861 | 8 |
| 322 | $\frac{5}{16}$ " x $2\frac{3}{4}$ " | $\frac{5}{16}$ " | 400002879 | 4 |
| 323 | $\frac{3}{8}$ " x 2" | $\frac{3}{8}$ " | 400002895 | 8 |
| 324 | $\frac{3}{8}$ " x $3\frac{1}{4}$ " | $\frac{3}{8}$ " | 400002903 | 4 |
| 325 | $\frac{1}{2}$ " x $2\frac{1}{4}$ " | $\frac{1}{2}$ " | 400002911 | 4 |
| 326 | $\frac{1}{2}$ " x $3\frac{1}{2}$ " | $\frac{1}{2}$ " | 400002937 | 4 |



C Drive Anchor

- Used to make temporary attachments in concrete and brick.
- Comprised of a shield and a double headed steel nail.
- Used in place of B Drive Anchors when temporary installations are required.
- Manufactured from AISI 1008 Steel.
- Zinc-plated to meet ASTM Specification B633, Class SC4, Type 1.
- Manufactured in the United States.

| PART NUMBER | SIZE | HOLE SIZE | BELL NUMBER | STD PKG |
|-------------|-------------------------------------|------------------|-------------|---------|
| 306 | $\frac{3}{16}$ " x $\frac{7}{8}$ " | $\frac{3}{16}$ " | 400002945 | 8 |
| 307 | $\frac{1}{4}$ " x 1" | $\frac{1}{4}$ " | 401711585 | 8 |
| 308 | $\frac{1}{4}$ " x $1\frac{1}{4}$ " | $\frac{1}{4}$ " | 400002978 | 8 |
| 309 | $\frac{1}{4}$ " x $1\frac{1}{2}$ " | $\frac{1}{4}$ " | 400002986 | 8 |
| 310 | $\frac{5}{16}$ " x $1\frac{1}{4}$ " | $\frac{5}{16}$ " | 400002994 | 8 |
| 311 | $\frac{5}{16}$ " x $1\frac{3}{4}$ " | $\frac{5}{16}$ " | 400003000 | 8 |
| 312 | $\frac{5}{16}$ " x $2\frac{1}{4}$ " | $\frac{5}{16}$ " | 400003018 | 4 |
| 313 | $\frac{5}{16}$ " x $2\frac{3}{4}$ " | $\frac{5}{16}$ " | 400003026 | 4 |
| 314 | $\frac{3}{8}$ " x 2" | $\frac{3}{8}$ " | 400003042 | 4 |
| 315 | $\frac{1}{2}$ " x $2\frac{1}{4}$ " | $\frac{1}{2}$ " | 400003067 | 4 |