


## Grade 8.2 Carbon Steel Mushroom Head Spike Anchor



- A one-piece, tamperproof and vibration resistant anchor for making attachments of medium weight (200-400 lbs.) in concrete, block, brick, or stone.
- The Spike Anchor is formed with an "S" shaped configuration at the working end of the anchor to create an expansion mechanism.
- The pre-expanded mechanism is activated as the anchor is driven into the drilled hole and creates a spring type compression force against the walls of the hole.
- Manufactured from Grade 8.2 Steel.
- Zinc plated to meet ASTM Specification B633 Class SC1, Type III.
- Manufactured in the United States.

PART NUMBER	SIZE	DRILL DIAMETER	HEAD SIZE (OD)	MINIMUM EMBEDMENT	STD PKG
7050	3/16" x 1"	3/16"	7/16"	7/8"	100
7051	3/16" x 1 1/4"	3/16"	7/16"	7/8"	100
7052	3/16" x 1 1/2"	3/16"	7/16"	1 1/4"	100
7053	3/16" x 2"	3/16"	7/16"	1 1/4"	100
7054	3/16" x 2 1/2"	3/16"	7/16"	1 1/4"	100
7055	3/16" x 3"	3/16"	7/16"	1 1/4"	100
7056	3/16" x 3 1/2"	3/16"	7/16"	1 1/4"	100
7057	3/16" x 4"	3/16"	7/16"	1 1/4"	100
7058	1/4" x 1"	1/4"	1/2"	7/8"	100
7059	1/4" x 1 1/4"	1/4"	1/2"	1"	100
7060	1/4" x 1 1/2"	1/4"	1/2"	1 1/4"	100
7061	1/4" x 2"	1/4"	1/2"	1 1/4"	100
7062	1/4" x 2 1/2"	1/4"	1/2"	1 1/4"	100
7063	1/4" x 3"	1/4"	1/2"	1 1/4"	100
7064	1/4" x 3 1/2"	1/4"	1/2"	1 1/4"	100
7065	1/4" x 4"	1/4"	1/2"	1 1/4"	100
7066	3/8" x 2"	3/8"	3/4"	1 3/4"	25
7067	3/8" x 2 1/2"	3/8"	3/4"	1 3/4"	25
7068	3/8" x 3"	3/8"	3/4"	1 3/4"	25
7069	3/8" x 3 1/2"	3/8"	3/4"	1 3/4"	25
7070	3/8" x 4"	3/8"	3/4"	1 3/4"	25
7071	3/8" x 5"	3/8"	3/4"	1 3/4"	25
7072	3/8" x 6"	3/8"	3/4"	1 3/4"	25
7073	1/2" x 3 1/2"	1/2"	1"	2 1/2"	25
7074	1/2" x 4"	1/2"	1"	2 1/2"	25
7075	1/2" x 5"	1/2"	1"	2 1/2"	25
7076	1/2" x 6"	1/2"	1"	2 1/2"	25