

## Lead Wood Screw Anchor



- Used with wood screws or tapping screws for anchoring lightweight attachments (under 100 lbs.) to concrete, block or brick.
- Withstands extreme changes in temperature.
- Not effected by chemicals or moisture.
- Ideal for shallow hole anchoring.
- Will conform to any irregularities in hole.
- Manufactured in the United States.

PART NUMBER	SIZE	HOLE DIAMETER	SSI NUMBER	STD PKG
176	#6-8 x 3/4"	1/4"	401130638	100
184	#6-8 x 1"	1/4"		100
177	#6-8 x 1 1/2"	1/4"	400473542	100
178	#10-14 x 1"	5/16"	997905567	100
179	#10-14 x 1 1/2"	5/16"	401130646	100
192	#16-18 x 1"	3/8"		50
191	#16-18 x 1 1/2"	3/8"	400473559	50
745	#20-24 x 1 3/4"	3/8"	400504791	125

## Lag Shield



- Used in conjunction with lag screws for attaching cable clamps, terminals, lock boxes, etc. to concrete, hollow block, and brick.
- Consists of two Zamac alloy sleeves which are held together by interlocking tabs.
- Tapered rings provide additional holding power in softer base materials.
- Internal threads to mate with lag screw threads.
- Manufactured from rustproof zinc alloy.
- Short style is used for hard masonry. The long style is used for soft masonry.
- Manufactured in the United States.

PART NUMBER	SIZE	HOLE SIZE	MINIMUM EMBEDMENT	STD PKG
1410*	1/4" Short	1/2"	1"	100
6003	5/16" Short	1/2"	1 1/4"	50
1412	3/8" Short	5/8"	1 3/4"	50
1413	1/2" Short	3/4"	2"	25
708*	1/4" Long	1/2"	1 1/2"	100
1415	5/16" Long	1/2"	1 3/4"	50
1416	3/8" Long	5/8"	2 1/2"	50
1417	1/2" Long	3/4"	3 1/2"	25

\* Ideal for installing P House Hooks into masonry.

## Machine Screw Anchor



- Used to fasten cable clamps in concrete, block, brick, and stone.
- Comprised of a lead sleeve and a threaded metal cone.
- Lead sleeve conforms to irregularities of hole.
- Toll required for installation.
- Manufactured in the United States.

PART NUMBER	SIZE	DRILL SIZE	ANCHOR LENGTH	BELL NUMBER	STD PKG
1400	#6-32	5/16"	1 7/32"		100
1401	#8-32	5/16"	1 7/32"		100
1402	#10-24	3/8"	1 1/16"		100
234	1/4-20	1/2"	7/8"	401125638	100
355	1/4-20 with 1 1/2" Bolt	1/2"	7/8"	700220692	25
1403	5/16-18 with 2" Bolt	5/8"	1 1/16"		25
1404	3/8-16 with 2" Bolt	3/4"	1 5/16"		25
356	1/2-13 with 2 1/2" Bolt	7/8"	1 9/16"	400487625	25