



## E Span Clamp

- Used in drop cable installations as an attachment to the strand for accepting the bail of Drop Wire Clamps.
- Tensile strength of jaws and bolt exceeds 75,000 P.S.I..
- Clamping range is from 1/4" (6.6M) to 7/16" (16M).
- Clamp is comprised of a pigtail bolt, two jaws, and a square nut.
- Bolt and nut are formed from Grade 2 Steel.
- Jaws are rolled and stamped from 1018 tempered Steel.
- Bolt and nut are hot dip galvanized to meet ASTM Specification A153, Class B3.
- Jaws are mechanically galvanized to meet ASTM Specification B695, Class 50, Type 1.
- Manufactured in the United States.

PART NUMBER	DESCRIPTION	BELL NUMBER	STD PKG
9055	E Span Clamp	400324489	5

4075



1705



## O Span Clamp

3003



- Used in drop cable installations as an attachment to strand for either accepting the bail of Drop Wire Clamps, or for wrapping the support wire of drop cable.
- Each clamp is comprised of a set of aluminum jaws, a shaped bolt, and a square nut.
- Also offered with two washers and an extra square nut for securing support wire of drop cable.
- Jaws are extruded and stamped from 6063-T6 Aluminum.
- Nuts, bolts, and washers are formed from Grade 2 Steel.
- All nuts, bolts, and washers are hot dip galvanized to meet ASTM Specification A153, Class B3.
- Attaches to strand ranging in size from 1/4" (6.6M) to 3/8" (10M).
- Manufactured in the United States.

PART NUMBER	DESCRIPTION	STD PKG
4075	O Span Clamp with One Square Nut	100
3003	O Span Clamp with Two Square Nuts and Two Washers	100
1705	O Span Clamp with Pigtail Bolt	100



## Q Span Clamp

- Used in drop cable installations as an attachment to strand for either accepting the bail of Drop Wire Clamps, or for wrapping the support wire of drop cable.
- Clamp consists of a set of steel jaws, a 1/4" diameter "pig-tail" shaped bolt, and a hex nut.
- The jaws are rolled and stamped from AISI 1018 tempered Steel.
- The bolt and hex nut are formed from Grade 2 Steel.
- Nut and bolt are hot dip galvanized to meet ASTM Specification A153, Class B3.
- Jaws are mechanically galvanized to meet ASTM Specification B695, Class 50, Type 1.
- Attaches to strand ranging in size from 1/4" (6.6M) to 7/16" (16M).
- Manufactured in the United States.

PART NUMBER	DESCRIPTION	STD PKG
4042	Q Span Clamp	25