

Stacker Kit

- Used as an attachment to the Multi-Drop Span Clamp to accommodate additional drops.
- Each kit is comprised of two retaining washers, a lock washer, and a hex nut.
- The retaining washers are manufactured from AISI 1018 Steel.
- The lock washer and hex nut are formed from Grade 2 Steel.
- Each component is mechanically galvanized to meet ASTM Specification B695, Class 50, Type 1.
- Manufactured in the United States.

PART NUMBER	DESCRIPTION	STD PKG
7021	Stacker Kit	1



SC Wire Clip for Telephone



S Clip for CATV


S Wire Clip

- Wire Clips are "S" shaped one piece aluminum clips.
- In phone applications, S Clips are used to secure the drip loop at the building. In CATV applications, S Clips are used to prevent separation of the coaxial cable from the support wire.
- S Clips for CATV are smooth. S Clips for phone have perforations for providing a positive hold on the drop cable.
- Stamped from 5052 Dead-Soft Aluminum.
- Manufactured in the United States.


PART NUMBER	DESCRIPTION	BELL NUMBER	STD PKG
905	S Clips for Messengered Coaxial Cable		100
906	S Clip for (2) Coaxial Cables		100
905P	SC Wire Clip for 1-2 Pair Drop Wire	400122560	25
908	SC Wire Clip for 6 Pair Drop Wire		25




8180



1015



1003



1005

Single Tap Bracket

- Used to secure a tap or other electronic device to strand.
- Consists of a bracket, a set of mating jaws, a carriage bolt and square nut.
- Attaches to strand ranging from 1/4" (6.6M) to 3/8" (10M).
- Aluminum brackets are stamped from 5052-H34 Aluminum.
- The aluminum jaws are extruded and stamped from 6063-T6 Aluminum.
- The carriage bolt and square nut are formed from Grade 2 Steel.
- Carriage bolt and square nut are hot dip galvanized to meet ASTM Specification A153, Class D.
- Manufactured in the United States.

PART NUMBER	DESCRIPTION	STD PKG
8180	1 1/2" Aluminum Tap Bracket	50
1003	2 1/2" Aluminum Tap Bracket	50
1015	2 1/2" Steel Tap Bracket	50
1005	2 1/2" Steel Tap Bracket with Bonding Connections for a 4-way Tap	50