

## B Masonry Clip

- Used to attach station wire and PBX (Private Board Exchange) cable to masonry and wood walls.
- Each clip provided with a  $\frac{7}{8}$ " nail.
- Clips are clear in appearance for aesthetics.
- Strain relief gripping of clips on cable allows installer not to hold clip while hammering.
- UV (Ultra Violet) light stabilized and weatherproofed to protect against natural elements.
- Nails are formed from hardened AISI 1050 Steel.
- Nails are zinc-plated to meet ASTM Specification B633, Class SC4, Type 1.
- Clips are molded from clear flame retardant polycarbonate.
- Smooth edges prevent damage to cable.



Masonry Clip



Drop Wire Clip

PART NUMBER	DESCRIPTION	CABLES ACCOMMODATED	NUMBER OF PINS	BELL NUMBER	STD PKG
802	B1 Masonry Clip	"D" Station Wire "H" Station Wire	2	402594907	10
803	B2 Masonry Clip	25 Pair PBX Cable	2	402594915	10
804	B3 Masonry Clip	25 Pair PBX Cable	1	402594923	10
805	Drop Wire Clip	1-2 Pair Drop Wire	2		10
806	4 Pair Drop Wire Clip	4 Pair Drop Wire	2		10

## Feed Thru Bushing

- Used to seal entry hole and protect cable.
- Molded from UV (Ultra Violet) resistant polypropylene.
- Manufactured in the United States.



PART NUMBER	SIZE	COLOR	STD PKG
864	RG-6	Black	100
865	RG-6	Ivory	100
866	RG-6 Quad Shield	Black	100
867	RG-6 Quad Shield	Ivory	100