

Hex Nuts (continued)**Grade 8 Steel Zinc Plated**

- Used in conjunction with Grade 8 bolts.
- Zinc plated to meet ASTM Specification B633, Class SC4, Type 1.
- Proof load is 150,000 psi.

PART NUMBER	INTERNAL THREAD SIZE	WIDTH ACROSS FLATS	THICKNESS	STD PKG
24910	1/4"-20	7/16"	7/32"	100
24920	5/16"-18	1/2"	17/64"	100
24930	3/8"-16	9/16"	21/64"	100
24940	1/2"-13	3/4"	7/16"	100
24950	5/8"-11	15/16"	35/64"	100
24960	3/4"-10	1 1/8"	41/64"	100

**18-8 Stainless Steel**

- Used in conjunction with 18-8 stainless bolts and machine screws.
- Rockwell Hardness ranges from B95-C32.
- Highly weather resistant.
- Proof load is 100,000 psi.

PART NUMBER	INTERNAL THREAD SIZE	WIDTH ACROSS FLATS	THICKNESS	STD PKG
24405	#6-32	5/16"	7/64"	100
24406	#8-32	11/32"	1/8"	100
24407	#10-24	3/8"	1/8"	100
24408	#10-32	3/8"	1/8"	100
24409	#12-24	7/16"	5/32"	100
182	1/4"-20	7/16"	3/16"	100
24410	1/4"-20	7/16"	7/32"	100
24420	5/16"-18	1/2"	17/64"	100
432	3/8"-16	9/16"	21/64"	100
24430	1/2"-13	3/4"	7/16"	100
24440	5/8"-11	15/64"	35/64"	100
24450	3/4"-10	1 1/8"	41/64"	100

**316 Stainless Steel**

- Used in conjunction with 316 Stainless Steel bolts.
- Highly weather resistant.
- Proof load is 100,000psi.
- 316 Stainless Steel is significantly more weather-resistant than 300 series Stainless Steel.

PART NUMBER	INTERNAL THREAD SIZE	WIDTH ACROSS FLATS	THICKNESS	STD PKG
54510	1/4"-20	7/16"	7/32"	100
54511	5/16"-18	1/2"	17/64"	100
54512	3/8"-16	9/16"	21/64"	100
54513	1/2"-13	3/4"	7/16"	100
54514	5/8"-11	15/16"	35/64"	100
54515	3/4"-10	1 1/8"	41/64"	100