

## Internal/External Tooth Lock Washer

- Heat-treated after stamping to a Rockwell Hardness of C40 to C50.
- Zinc plated to meet ASTM Specification B633 SC4, Type 1.



PART NUMBER	SCREW SIZE	INSIDE DIA.	OUTSIDE DIA.	THICKNESS (min.)	STD PKG
10210	#6	.141" - .150"	.495" - .510"	.023"	1000
10220	#8	.163" - .176"	.580" - .610"	.023"	1000
10230	#10	.195" - .204"	.580" - .610"	.028"	1000
10240	1/4"	.256" - .267"	.725" - .760"	.032"	1000
10250	5/16"	.320" - .332"	.865" - .900"	.032"	1000
10260	3/8"	.384" - .398"	.965" - .985"	.037"	1000
10280	1/2"	.512" - .530"	1.22" - 1.26"	.047"	1000
10292	5/8"	.640" - .663"	1.38" - 1.41"	.052"	250

## Internal Tooth Lock Washer


- Heat-treated after stamping to a Rockwell Hardness C40 to C50.
- Zinc plated to meet ASTM Specification B633 SC4, Type 1.



PART NUMBER	SCREW SIZE	OUTSIDE DIA. (min.)	THICKNESS (min.)	STD PKG
10310	#6	.275" - .295"	.017"	1000
10311	#8	.325" - .340"	.018"	1000
10312	#10	.365" - .381"	.020"	1000
10313	1/4"	.460" - .478"	.023"	1000
10314	5/16"	.594" - .610"	.028"	1000
10315	3/8"	.670" - .692"	.032"	1000
10317	1/2"	.867" - .900"	.037"	1000
10319	5/8"	1.045" - 1.071"	.042"	250

## External Tooth Lock Washer

- Heat-treated after stamping to a Rockwell Hardness of C40 to C50.
- Zinc plated to meet ASTM Specification B633 SC4, Type 1.



PART NUMBER	SCREW SIZE	OUTSIDE DIAMETER	THICKNESS (min.)	STD PKG
24210	#6	.305" - .320"	.024"	1000
24220	#8	.365" - .381"	.024"	1000
24230	#10	.395" - .410"	.024"	1000
782	1/4"	.494" - .510"	.027"	1000
24340	5/16"	.588" - .610"	.033"	1000
1300	3/8"	.670" - .694"	.042"	100
24360	1/2"	.880" - .900"	.048"	1000
24380	5/8"	1.045" - 1.070"	.054"	250
24390	3/4"	1.220" - 1.260"	.054"	100