



Plain




Galvanized

F436-1 Structural Washer

- Dimensionally comparable to the USS Washer, but with a smaller outside diameter and manufactured from a higher grade of steel and heat-treated.
- Designed to be used with A325 Structural Bolts.
- Rockwell Hardness ranges from C38-45.
- Galvanized washers conform to ASTM Specification A153 Class D.
- Manufactured in the United States.
- Fully traceable certifications of chemical and physical compliance available by request.

PART NUMBER	SIZE	OUTSIDE DIAMETER (max.)	THICKNESS	PLATING	STD PKG
5245	1/2"	1.094"	31/64"	Plain	1000
5246	5/8"	1.344"	39/64"	Plain	900
5247	3/4"	1.500"	47/64"	Plain	500
5248	7/8"	1.781"	55/64"	Plain	300
5249	1/2"	1.094"	31/64"	Galvanized	1000
5250	5/8"	1.344"	39/64"	Galvanized	900
5251	3/4"	1.500"	47/64"	Galvanized	500
5252	7/8"	1.781"	55/64"	Galvanized	300

Slotted Hex Washer AB Tapping Screw Stainless Steel



- Used to "tap" their own mating internal thread when driven into preformed holes in metallic materials.
- All sizes are fully threaded.
- Does not require a preformed hole in wood.
- Formed from 18-8 Stainless Steel for strength and weather resistance.

PART NUMBER	SIZE	HEX SIZE	STD PKG
20000	#6 x 1/2"	1/4"	100
69700	#6 x 3/4"	1/4"	100
82000	#6 x 1"	1/4"	100
20400	#8 x 1/2"	1/4"	100
13600	#8 x 3/4"	1/4"	100
13800	#8 x 1"	1/4"	100
13500	#8 x 1 1/4"	1/4"	100
13900	#8 x 1 1/2"	1/4"	100
14000	#8 x 2"	1/4"	100
28800	#10 x 1/2"	5/16"	100
66700	#10 x 3/4"	5/16"	100
66800	#10 x 1"	5/16"	100
66900	#10 x 1 1/4"	5/16"	100
38800	#10 x 1 1/2"	5/16"	100
45700	#10 x 2"	5/16"	100
1550	#10 x 2 1/2"	5/16"	100
19800	#14 x 3/4"	3/8"	100
18900	#14 x 1"	3/8"	100
19000	#14 x 1 1/2"	3/8"	100
38900	#14 x 2"	3/8"	100