

Slotted Hex Washer AB Tapping Screw

- Used to “tap” their own mating internal thread when driven into preformed holes in metallic materials.
- Does not require a preformed hole in wood.
- Case hardened so surface has a minimum Rockwell Hardness of C45.
- Manufactured from AISI 1016 steel.
- Saw slotted for deep even groove.
- All sizes are fully threaded.
- Zinc plated to meet ASTM Specification B633, SC4, Type 1.



PART NUMBER	SIZE	HEX SIZE	STD PKG
2010	#6 x 1/4"	1/4"	100
200	#6 x 1/2"	1/4"	100
81	#6 x 5/8"	1/4"	100
697	#6 x 3/4"	1/4"	100
82	#6 x 1"	1/4"	100
204	#8 x 1/2"	1/4"	20
134	#8 x 1/2"	1/4"	100
137	#8 x 5/8"	1/4"	100
201	#8 x 3/4"	1/4"	20
136	#8 x 3/4"	1/4"	100
205	#8 x 1"	1/4"	20
138	#8 x 1"	1/4"	100
202	#8 x 1 1/4"	1/4"	20
135	#8 x 1 1/4"	1/4"	100
384	#8 x 1 1/2"	1/4"	8
139	#8 x 1 1/2"	1/4"	100
385	#8 x 2"	1/4"	20
140	#8 x 2"	1/4"	100
383	#8 x 2 1/2"	1/4"	100
458	#8 x 3"	1/4"	100
288	#10 x 1/2"	5/16"	100
667	#10 x 3/4"	5/16"	100
668	#10 x 1"	5/16"	100
669	#10 x 1 1/4"	5/16"	100
388	#10 x 1 1/2"	5/16"	100
457	#10 x 2"	5/16"	100
155	#10 x 2 1/2"	5/16"	100
390	#10 x 3"	5/16"	100
396	#10 x 4"	5/16"	100
392	#10 x 4"	5/16"	8
212300	#12 x 3/4"	5/16"	100
173	#12 x 1"	5/16"	100
145	#12 x 1 1/2"	5/16"	100
397	#12 x 2"	5/16"	100
198	#14 x 3/4"	3/8"	100
189	#14 x 1"	3/8"	100
142	#14 x 1 1/4"	3/8"	100
386	#14 x 1 1/2"	3/8"	20
190	#14 x 1 1/2"	3/8"	100
8030	#14 x 1 3/4"	3/8"	100
389	#14 x 2"	3/8"	100
156	#14 x 2 1/2"	3/8"	100
199	#14 x 3"	3/8"	100
748	#14 x 4"	3/8"	100
158	#18 x 1 1/2"	3/8"	100
159	#18 x 2"	3/8"	100
225	#18 x 2"	3/8"	8
160	#18 x 2 1/2"	3/8"	100
226	#18 x 2 1/2"	3/8"	8