

Two Piece Trailer Ground Clamp

- Used to bond ground wire to I beams or other steel structures.
- Clamp is comprised of two mating bronze castings that are tin-plated to prevent corrosion.
- Top and bottom casting have integral teeth to penetrate oxidation or paint for positive ground.
- Ground Stud accepts #14-#6 SOL ground wire.
- Ground stud and mating screw formed from Brass and nickel plated to prevent dissimilar metal contact.
- Manufactured in the United States.



PART NUMBER	DESCRIPTION	BELL NUMBER	STD PKG
9840	Two Piece Trailer Ground Clamp	000213140	10

Grounding Tap Bracket


- Used to mount a tap and to provide a ground connection for up to a #6 AWG ground wire.
- Bracket height is $\frac{3}{4}$ " to provide adequate clearance for installing taps in MDU boxes.
- Overall length of bracket is $6\frac{1}{2}$ ".
- Stamped from 304 Stainless Steel.
- Center mounting hole is .446".
- Manufactured in the United States.



PART NUMBER	DESCRIPTION	STOCK SIZE	MOUNTING HOLE DIAMETERS	STD PKG
2150	Tap Bracket with Ground Lug	.048 x 1"	$\frac{9}{32}$ "	100

B Ground Wire Clamp

- Used to secure #6 AWG through #12 AWG ground wire runs.
- Stamped from AISI 1018 Steel.
- Mechanically galvanized to meet ASTM Specification B695, Class 50, Type 1.
- $\frac{7}{32}$ " Screw hole (accommodates #8 - #12 Screws).
- Manufactured in the United States.



PART NUMBER	DESCRIPTION	STOCK SIZE	STD PKG
9050	B Ground Wire Clamp	.035 x $\frac{3}{8}$ "	500

Ground Wire Nail

- Used to fasten #6-14 AWG ground wire to woodwork.
- Ground Wire Nails come with a diamond shaped point for easy installation.
- Formed from AISI 1018 Hardened Steel.
- Zinc Plated to meet ASTM Specification B633, Class SC4, Type 11.
- Manufactured in the United States.



PART NUMBER	SIZE	BELL NUMBER	PIECES PER LB.	STD PKG
739	$\frac{7}{8}$ "	400162244	561	1 lb.
740	$1\frac{3}{8}$ "	400162251	275	1 lb.