


B Cable Suspension Bolt

- Used to secure two cable suspension clamps at opposite sides of utility pole.
- Each threaded bolt is supplied with four attached regular square nuts.
- Bolt provided with cone point at each end to ease starting.
- Hot dip galvanized to meet ASTM Specification A153, Class C.
- Allied Bolt marking (AB) and tensile load designation mark (i.e.: 10M, 16M, 25M) appear on unthreaded portion of each bolt.
- Minimum tensile strength:
5/8" – 13,550 lbf., 3/4" – 20,050 lbf.
- Manufactured in the United States.

PART NUMBER	SIZE	UNTHREADED SECTION	BELL NUMBER	STD PKG
8260	5/8" x 10"	4"	400013777	50
8261	5/8" x 12"	4"	400013785	40
8262	5/8" x 14"	2"	400013793	30
8263	5/8" x 16"	4"	400013801	25
8264	5/8" x 18"	6"	400013819	25
8271	5/8" x 20"	6"	400013827	10
8272	5/8" x 22"	6"	400013835	10
8273	5/8" x 24"	6"		10
8274	5/8" x 25"	6"		5
8275	5/8" x 28"	6"		5
8276	5/8" x 30"	6"		5
8320	3/4" x 10"	4"		25
8321	3/4" x 12"	4"	400013850	25
8322	3/4" x 14"	2"	400013868	25
8323	3/4" x 16"	4"	400013876	20
8324	3/4" x 18"	6"	400013884	10
8325	3/4" x 20"	6"	400013892	5
8326	3/4" x 22"	6"		5
8327	3/4" x 24"	6"		5
8328	3/4" x 26"	6"		5
8329	3/4" x 28"	6"		5
8332	3/4" x 30"	6"		5



Double Arming Bolt

- Used to secure two cable suspension clamps or other attachments on opposite sides of utility pole.
- Each Double Arming Bolt is supplied with four attached square nuts.
- Bolt provided with cone point at each end to ease starting.
- Hot dip galvanized to meet ASTM Specification A153, Class C.
- Minimum tensile strength:
5/8" – 13,550 lbf., 3/4" – 20,050 lbf.,
7/8" – 27,700 lbf.
- Manufactured in the United States.

PART NUMBER	SIZE	STD PKG
59750	3/8" x 8"	25
59755	1/2" x 18"	25
5950	5/8" x 10"	25
5952	5/8" x 12"	25
5954	5/8" x 14"	25
5956	5/8" x 16"	25
5958	5/8" x 18"	25
5960	5/8" x 20"	25
5962	5/8" x 22"	25
5964	5/8" x 24"	25