

Spline Drive SDS Rotary Hammer Drill Bit

- Used in a rotary hammer machine equipped with a Spline Drive chuck.
- Used for high speed drilling in masonry, stone, brick, and aggregates.
- Undercut helical fluting is formed with small lands to minimize contact with the wall of the drill hole.
- The unique shank configuration fits most models of rotary hammer drills providing maximum drilling torque.
- Constructed from tungsten for extra long life.
- Manufactured in the United States.



PART NUMBER	DRILL SIZE	OVERALL LENGTH	DRILLING DEPTH	STD PKG
58700	3/8"	8"	3"	1
58701	3/8"	11"	6"	1
58702	3/8"	16"	11"	1
58703	7/16"	13"	8"	1
58704	1/2"	11"	6"	1
58705	1/2"	16"	11"	1
58706	1/2"	23"	18"	1
58707	1/2"	27"	22"	1
58708	1/2"	36"	31"	1
58709	9/16"	11"	6"	1
58710	9/16"	16"	11"	1
58711	9/16"	23"	18"	1
58712	9/16"	27"	22"	1
58713	5/8"	11"	6"	1
58714	5/8"	16"	11"	1
58715	5/8"	23"	18"	1
58716	5/8"	27"	22"	1
58717	5/8"	36"	31"	1
58718	11/16"	13"	8"	1
58719	11/16"	16"	11"	1
58720	3/4"	11"	6"	1
58721	3/4"	16"	11"	1
58722	3/4"	23"	18"	1
58723	3/4"	27"	22"	1
58724	3/4"	36"	31"	1
58725	27/32"	16"	11"	1
58726	7/8"	16"	11"	1
58727	7/8"	23"	18"	1
58728	7/8"	36"	31"	1
58729	1"	13"	8"	1
58730	1"	16"	11"	1
58731	1"	23"	18"	1
58732	1"	36"	31"	1
58733	1 1/8"	16"	11"	1
58734	1 1/8"	23"	18"	1
58735	1 1/4"	16"	11"	1
58736	1 1/4"	23"	18"	1
58737	1 1/4"	36"	31"	1
58738	1 3/8"	16"	11"	1
58739	1 3/8"	23"	18"	1
58740	1 1/2"	16"	11"	1
58741	1 1/2"	23"	18"	1
58742	1 3/4"	23"	18"	1
58743	2"	23"	18"	1