



Spline Drive X Cutter SDS Drill

- For use in rotary hammer machines equipped with a Spline Drive type chuck.
- The head has four cutting faces that reduces vibration up to 60% and noise up to 30%.
- Four-way head allows easy spotting and rounder holes.
- Undercut helical fluting is formed with small lands to minimize contact with the wall of the drill hole.
- The taper core improves the transmission of impact energy to the bit tip for faster drilling.
- The shaft is annealed to prevent breakage.
- Special tungsten carbide tip.
- Copper silver brazing of carbide head.
- Double spiral for fastest debris removal.
- Suitable for masonry, stone, brick and aggregates.



PART NUMBER	DRILL SIZE	OVERALL LENGTH	DRILLING DEPTH	STD PKG
58800	5/8"	10"	5"	1
58801	5/8"	16"	11"	1
58802	5/8"	22"	17"	1
58803	5/8"	29"	24"	1
58804	5/8"	36"	31"	1
58805	3/4"	10"	5"	1
58806	3/4"	16"	11"	1
58807	3/4"	22"	17"	1
58808	3/4"	29"	24"	1
58809	3/4"	36"	31"	1
58810	7/8"	16"	11"	1
58811	7/8"	22"	17"	1
58812	1"	16"	11"	1
58813	1"	22"	17"	1
58814	1"	29"	24"	1
58815	1"	36"	31"	1
58816	1 1/8"	16"	11"	1
58817	1 1/8"	22"	17"	1
58818	1 1/4"	16"	11"	1
58819	1 1/4"	22"	17"	1
58820	1 1/4"	29"	24"	1
58821	1 1/4"	36"	31"	1
58822	1 3/8"	16"	11"	1
58823	1 3/8"	22"	17"	1
58824	1 1/2"	22"	17"	1

Bits compatible with the following machines:

AEG®

PH38 PHD26
PHD38 PH240D

B&D®

5041 5042
5043 5044K
5045K 5059
5093K 5095K
5096K 5098K

Metabo®

RH66 RH99X
1129 1130
6030 6040
6046

Milwaukee®

5309 5311
5316 5318-21
5319-21 5321-22
5341 5343
5344 5345-21
5347 5348
5352

Kango®

430S 501S
637S 750S
950S 978S

Bosch®

11202 11203
11204 11205
11209 11214
11219 11220
11232EVS 11233EVS
11244E 11247
11248EVS 11314

Red Head®

747-2

Ramset®

442 445
475

Makita®

HR3851 HR4040C
HR5000

Dewalt®

530K 531K
532K 533K
D25650K D25550K
D25551K

Hitachi®

DH38YE(G) DH40FA
DH40FB DS50SB(K)

Ryobi®

ED382P ER382

Wacker®

EBH 10