

Hex Nut



Grade 2 Steel Zinc Plated

- Used in conjunction with low carbon bolts and screws that are not treated.
- Formed from Grade 2 steel.
- Rockwell Hardness ranges from B68-C32.
- Zinc plated to meet ASTM Specification B633, Class SC4, Type 1.
- Proof load is 90,000 psi.

PART NUMBER	INTERNAL THREAD SIZE	WIDTH ACROSS FLATS	THICKNESS	STD PKG
164	#6-32	5/16"	7/64"	100
165	#8-32	11/32"	1/8"	100
1250	#10-24	3/8"	1/8"	100
1265	#10-32	3/8"	1/8"	100
1267	#12-24	7/16"	5/32"	100
168	1/4"-20	7/16"	3/16"	100
371	1/4"-20	7/16"	7/32"	100
243	5/16"-18	1/2"	17/64"	100
660	3/8"-16	9/16"	21/64"	100
583	1/2"-13	3/4"	7/16"	100
1286	5/8"-11	15/16"	35/64"	100
1310	3/4"-10	1 1/8"	41/64"	100

Grade 2 Steel Galvanized

- Used in conjunction with low carbon galvanized bolts.
- Tapped oversized after plating to ensure easy fit on bolts.
- Hot dip galvanized to meet ASTM Specification A153, Class D.
- Proof load is 68,000 psi.



PART NUMBER	INTERNAL THREAD SIZE	WIDTH ACROSS FLATS	THICKNESS	STD PKG
542	1/4"-20	7/16"	7/32"	100
24710	5/16"-18	1/2"	17/64"	100
24720	3/8"-16	9/16"	21/64"	100
24730	1/2"-13	3/4"	7/16"	100
24740	5/8"-11	15/16"	35/64"	100
24750	3/4"-10	1 1/8"	41/64"	100

Grade 5 Steel Zinc Plated

- Used in conjunction with Grade 5 bolts.
- Zinc plated to meet ASTM Specification B633, Class SC4, Type 1.
- Proof load is 120,000 psi.



PART NUMBER	INTERNAL THREAD SIZE	WIDTH ACROSS FLATS	THICKNESS	STD PKG
24810	1/4"-20	7/16"	7/32"	100
24820	5/16"-18	1/2"	17/64"	100
24830	3/8"-16	9/16"	21/64"	100
24840	1/2"-13	3/4"	7/16"	100
24850	5/8"-11	15/16"	35/64"	100
24860	3/4"-10	1 1/8"	41/64"	100